M2M CONTROL Comparsion Chart

Product	GSM - World wide Quadband	2G (GPRS), 3G (UMTS, HSDPA)	On-Board Ethernet	Dual SIM support	SIM Chip prepared	GNSS receiver (GPS/GLONASS/QZSS)	Super GPS Receiver	3D G-Sensor	RF ISM Transceiver (868 Mhz)	Interactive Voice Response / DMTF	RS-232 Interfaces	RS-485 Interfaces	CAN 2.0B Interface	1-Wire Interface	Digital Inputs	Digital Outputs Solid State	Digital Outputs Relay	Analog Inputs	Analog Outputs	Power Supply 10-36 VDC	Power Supply 100-260 VAC	Internal battery Backup (Ah)	Power Management	SD-Card with FAT Filesystem	Internal Flash Drive with FAT (MB)	Automatic Datalogger (MB)	Persistent Flash	System Flash Memory (MB)	NVRAM Memory (KB)	RAM Memory (MB)
C360	•	3G		•					•	2	(2)	•	•	8	8		4	4	•		2	•	•	4	1	3.5	2.2	8	1	
C350	•	2G		•					•	2	(2)	•	•	8	8		4	4	•		2	•	•	4	1	3.5	2.2	8	1	
C310	•	2G		•						1	1		•	8	8		4	4	•		1	•		4	1	3.5	2.2	8	1	
C305	•	2G		•						1				5	4		2	2	•		1	•		4	1	3.5	2.2	8	1	
C460	•	3G	•		•			•	•	2	(2)		•	5		4	4	4	•	•	2	•	•	8	1	7.5	4.5	20	2	
C450	•	2G			•			•	•	2	(2)		•	5		4	4	4	•	•	2	•	•	4	1	3.5	2.2	8	1	
C410	•	2G			•					1			•	5		4	2		•	•	1	•		4	1	3.5	2.2	8	1	
C520	•	3G			•	•		•	•	1			•	2			1		•		0.9	•	•	4	1	3.5	2.2	8	1	
C521	•	3G			•	•		•	•			•		2			1		•		0.9	•	•	4	1	3.5	2.2	8	1	
C550	•	2G			•		•	•	•	1			•	2	2		2		•		(58)	•	•	0.5	0.5	0.5	2.2	8	1	
C650	•	3G		•	•	•	•	•		•	2	1	•	•	5	4		2		•		2	•	•	8	1	7.5	4.5	20	2	
C600	•	2G		•	•	•	•	•		•	2	1	•	•	5	4		2		•		2	•	•	8	1	7.5	4.5	20	2	
C610	•	2G		•	•	•	•	•		•	1				5	4				•		2	•		4	1	3.5	4.5	20	2	