

# M2M CONTROL Comparison Chart



Product	GSM	Cellular Interface	On-Board Ethernet	WLAN / Bluetooth / WM-Bus (M)	SIM Chip prepared	GNSS receiver (GPS/GLONASS/QZSS)	Super GPS Receiver	3D G-Sensor	RF ISM Transceiver (868 Mhz)	Interactive Voice Response / DMTF	RS-232 Interfaces	RS-485 Interfaces	CAN 2.0B Interface	1-Wire Interface	Digital Inputs	Digital Outputs Solid State	Analog Inputs	Analog Outputs	Power Supply 10-36 VDC	Power Supply 100-260 VAC	Internal battery Backup (Ah)	Power Management	SD-Card with FAT Filesystem	Internal Flash Drive with FAT (MB)	Automatic Datalogger (MB)	Persistent Flash	System Flash Memory (MB)	NVRAM Memory (KB)	RAM Memory (MB)
CX360	•	4G	•	•	•	•	•	•	•	2	2	•	•	8	8	4	4	•	2	•	•	32	1	16	512	8	128		
CX351	•	3G	•	M	•	•	•	•	•	2	2	•	•	8	8	4	4	•	2	•	•	32	1	16	512	8	128		
CX350	•	3G	•	•	•	•	•	•	•	2	2	•	•	8	8	4	4	•	2	•	•	32	1	16	512	8	128		
C370	•	NB	•	•	•	•	•	•	•	2	(2)	•	•	8	8	4	4	•	2	•	•	4	1	3.5	2.2	8	1		
C360	•	3G	•	•	•	•	•	•	•	2	(2)	•	•	8	8	4	4	•	2	•	•	4	1	3.5	2.2	8	1		
C350	•	2G	•	•	•	•	•	•	•	2	(2)	•	•	8	8	4	4	•	2	•	•	4	1	3.5	2.2	8	1		
C310	•	2G	•	•	•	•	•	•	•	1	1	•	•	8	8	4	4	•	1	•	•	4	1	3.5	2.2	8	1		
C305	•	2G	•	•	•	•	•	•	•	1	•	•	•	5	4	2	2	•	1	•	•	4	1	3.5	2.2	8	1		
C460	•	3G	•	•	•	•	•	•	•	2	(2)	•	•	5	4	4	4	•	•	2	•	•	8	1	7.5	4.5	20	2	
C450	•	2G	•	•	•	•	•	•	•	2	(2)	•	•	5	4	4	4	•	•	2	•	•	4	1	3.5	2.2	8	1	
C410	•	2G	•	•	•	•	•	•	•	1	•	•	•	5	4	2	•	•	1	•	•	4	1	3.5	2.2	8	1		
C520	•	3G	•	•	•	•	•	•	•	1	•	•	•	2	1	•	•	•	0.9	•	•	4	1	3.5	2.2	8	1		
C521	•	3G	•	•	•	•	•	•	•	•	•	•	•	2	1	•	•	•	0.9	•	•	4	1	3.5	2.2	8	1		
C550	•	2G	•	•	•	•	•	•	•	1	•	•	•	2	2	2	•	•	(58)	•	•	0.5	0.5	0.5	2.2	8	1		
C650	•	3G	•	•	•	•	•	•	•	2	1	•	•	5	4	2	•	•	2	•	•	8	1	7.5	4.5	20	2		
C600	•	2G	•	•	•	•	•	•	•	2	1	•	•	5	4	2	•	•	2	•	•	8	1	7.5	4.5	20	2		
C610	•	2G	•	•	•	•	•	•	•	1	•	•	•	5	4	2	•	•	2	•	•	4	1	3.5	4.5	20	2		