

M2M CONTROL Comparsion Chart



Product	GSM	Cellular Interface	On-Board Ethernet	WLAN / Bluetooth / WM-Bus (M)	SIM Chip prepared	GNSS receiver (GPS/GLONASS/QZSS)	3D G-Sensor	RF ISM Transceiver (868 MHz)	Interactive Voice Response / DMTF	RS-232 Interfaces	RS-485 Interfaces	CAN 2.0B Interface	wired M-Bus Master (loads)	Digital Inputs	Digital Outputs Solid State	Analog Inputs	Analog Outputs	Power Supply 10-36 VDC	Power Supply 100-260 VAC	Internal battery Backup (Ah)	Power Management	SD-Card with FAT Filesystem	Automatic Datalogger with FAT (MB)	Persistent Flash	System Flash Memory (MB)	NVRAM Memory (KB)	RAM Memory (MB)	
CX365	●	4G	●	●	●			●	●	2	2	●	●	8	8	4	4	●	2	●	●	512	8	16	512	8	128	
CX360	●	4G	●	●	●			●	●	2	2	●	●	8	8	4	4	●	2	●	●	512	8	16	512	8	128	
CX361	●	4G	●	M	●			●	●	2	2	●	●	8	8	4	4	●	2	●	●	512	8	16	512	8	128	
CX320	●	4G	●		●			●		1	2		20	●	8	8	4	2	●	2	●	●	64	32	7	256	8	128
CX321	●	4G	●	M	●			●		1	2		20	●	8	8	4	2	●	2	●	●	64	32	7	256	8	128
C370	●	NB			●			●		2	(2)	●		●	8	8	4	4	●	2	●	●	4	1	3.5	2.2	8	1
CX460	●	4G	●	●	●	●	●	●	●	2	2			●	5	4	4	●	●	2	●	●	512	1	16	512	8	128
CX410	●	4G	●		●			●		2	2			●	5	4	2	●	●	1	●	●	512	1	16	512	8	128
C410	●	2G		●				1				●	5	4	2		●	●	1	●		4	1	3.5	2.2	8	1	
CX530	●	4G	●	●	●	●	●	●	●	1	1	●		●	3	4	2		●	2	●	●	128	1	16	512	8	128
CX510	●	4G		●	●	●	●	●	●	1	1	●		●	3	4		●	1	●		64	1	16	512	8	128	
C520	●	3G		●	●		●	●	1			●	2		1		●	0.9	●	●	4 GB	1	3.5	2.2	8	1		
C521	●	3G		●	●		●	●				●	2		1		●	0.9	●	●	4 GB	1	3.5	2.2	8	1		
CX660	●	4G	●	●	●	●	●	●	●	2	1	2		●	5/4	4	2/4		●	2	●	●	512	1	16	512	8	128
CX630	●	4G	BT	●	●	●	●	●	●	2	1	2		●	6	4	2		●	2	●		4 GB	1	16	512	8	128
C660	●	4G		●	●	●	●	●	●	2	1	●		●	5	4	2		●	2	●	●	8	1	7.5	4.5	20	2
C610	●	2G		●	●	●	●	●	●	1				●	5	4	2		●	2	●		4	1	3.5	4.5	20	2