M2M CONTROL Comparsion Chart

Product	GSM	Cellular Interface	On-Board Ethernet	WLAN / Bluetooth / WM-Bus (M)	SIM Chip prepared	GNSS receiver (GPS/GLONASS/QZSS)	Super GPS Receiver	3D G-Sensor	RF ISM Transceiver (868 Mhz)	Interactive Voice Response / DMTF	RS-232 Interfaces	RS-485 Interfaces	CAN 2.0B Interface	1-Wire Interface	Digital Inputs	Digital Outputs Solid State	Digital Outputs Relay	Analog Inputs	Analog Outputs	Power Supply 10-36 VDC	Power Supply 100-260 VAC	Internal battery Backup (Ah)	Power Management	SD-Card with FAT Filesystem	Internal Flash Drive with FAT (MB)	Automatic Datalogger (MB)	Persistent Flash	System Flash Memory (MB)	NVRAM Memory (KB)	RAM Memory (MB)
CX360	●	4G	●	●	●				●	●	2	2	●	●	8	8		4	4	●		2	●	●	32	1	16	512	8	128
CX351	●	3G	●	M	●				●	●	2	2	●	●	8	8		4	4	●		2	●	●	32	1	16	512	8	128
CX350	●	3G	●	●	●				●	●	2	2	●	●	8	8		4	4	●		2	●	●	32	1	16	512	8	128
C370	●	NB			●					●	2	(2)	●	●	8	8		4	4	●		2	●	●	4	1	3.5	2.2	8	1
C360	●	3G			●					●	2	(2)	●	●	8	8		4	4	●		2	●	●	4	1	3.5	2.2	8	1
C350	●	2G			●					●	2	(2)	●	●	8	8		4	4	●		2	●	●	4	1	3.5	2.2	8	1
C310	●	2G			●						1	1		●	8	8		4	4	●		1	●		4	1	3.5	2.2	8	1
C305	●	2G			●						1				5	4		2	2	●		1	●		4	1	3.5	2.2	8	1
CX460	●	4G	●	●	●	●		●	●	●	2	(2)		●	5		4	4	4	●	●	2	●	●	32	1	16	512	8	128
C460	●	3G	●		●				●	●	2	(2)		●	5		4	4	4	●	●	2	●	●	8	1	7.5	4.5	20	2
C450	●	2G			●				●	●	2	(2)		●	5		4	4	4	●	●	2	●	●	4	1	3.5	2.2	8	1
C410	●	2G			●						1			●	5		4	2		●	●	1	●		4	1	3.5	2.2	8	1
C520	●	3G			●	●		●	●		1			●	2			1		●		0.9	●	●	4	1	3.5	2.2	8	1
C521	●	3G			●	●		●	●				●		2			1		●		0.9	●	●	4	1	3.5	2.2	8	1
C550	●	2G			●		●	●	●		1			●	2	2		2		●		(58)	●	●	0.5	0.5	0.5	2.2	8	1
CX660	●	4G	●	●	●	●	●	●		●	2	1	●	●	5/4	4		2/4		●		2	●	●	32	1	16	512	8	128
C660	●	4G			●	●	●	●		●	2	1	●	●	5	4		2		●		2	●	●	8	1	7.5	4.5	20	2
C650	●	3G			●	●	●	●		●	2	1	●	●	5	4		2		●		2	●	●	8	1	7.5	4.5	20	2
C600	●	2G			●	●	●	●		●	2	1	●	●	5	4		2		●		2	●	●	8	1	7.5	4.5	20	2
C610	●	2G			●	●	●	●		●	1				5	4		2		●		2	●		4	1	3.5	4.5	20	2